



Front

Back



Product Specs

Bolt

- 3/8"-16 x 1.5" Attachment Bolt*
- Material Type: 304 Stainless Steel

Plate

- Outer Diameter: 5-1/2"
- Fastener Hole Diameter: 17/64" (8 holes)
- Fastener Hole Pattern: 4-1/8" Diameter
- Material Thickness: 0.047" (1.194mm)
- Material Type: Galvalume® AZ55

Cover Membrane

- Manufacturer: Brand Specific OR Generic
- Color: Default Black*
- Length: 11.75"
- Width: 11.75"
- Thickness: Default 60 mil*

Patents

- Visit www.anchorp.com/patents

Packaging Specs

- Sold Individually OR Full Box Quantity
- Individual Weight: Approx. 0.75 lbs
- Full Box Quantity: 10 units
- Box Weight: Approx. 10 lbs
- Box Dimensions: 17" x 17" x 5"
- Full Pallet Quantity: 40 boxes
- Pallet Dimensions: 48" x 40" x 52"

* Specified option is standard. Custom options may be available for additional charge. Lead times may apply depending on roofing manufacturer and product availability.

Description

The U2400-EPDM is a lightweight rooftop attachment system consisting of a U-Anchor 2000 Series plate and cover membrane. The cover membrane is factory cut and installed in the field. The U2400-EPDM provides a positive, watertight, manufacturer accepted attachment for mechanically attached and fully adhered EPDM single-ply membranes.

Advantages

- Extremely strong and lightweight.
- Fast installation, approximate rate of 12 per man hour.
- Installs on any surface from flat to vertical.

U-Anchor Attachment

The U2400-EPDM is attached by fastening through the roofing assembly into the structural decking with 2-8 approved fasteners. The membrane cover is then adhered in place and sealed around the perimeter to the cover membrane.

Fastener selection is dictated by the system assembly, deck type, and the project engineer.

Refer to installation instructions and the specified roofing material manufacturer requirements before installing.

Equipment Attachment

To securely mount your rooftop equipment to the U-Anchor, after its installed, the connection nut must be fastened to approximately 20-25 torque pounds.

Use a calibrated torque wrench during install to ensure appropriate results are achieved.

Testing / Approvals

- Accepted - All Major Roofing Manufacturers
- LARR Listed

Individual deck assembly reports available upon request.

Ratings

Results are base on plate performance only.

- Ultimate Load - Shear: 4000 lbs
- Ultimate Load - Tension: 3000 lbs

*Test was performed in accordance with:
ICC-ES AC467 Section 3.2*

Warranty

- Standard 20 Year Material Only Warranty

