



Front

Back



Product Specs

Bolt

- 3/8"-16 x 1.5" Bolt*
- Material Type: 304 Stainless Steel

Plate

Dimensions: 11.08" x 5.47"

- Fastener Hole Diameter: 17/64" (12 holes)
- Material Thickness: 0.047" (1.194mm)
- Material Type: Galvalume® AZ55
- Target Membrane
- Manufacturer: Brand Specific OR Generic
- Color: Default White*
- Length: 21.5"
- Width: 15.75"
- Thickness: Approx. 60 mils*

Patents

- Visit www.anchorp.com/patents

Packaging Specs

- Sold Individually OR Full Box Quantity
- Individual Weight: Approx. 2 lbs
- Full Box Quantity: 10 units
- Box Weight: Approx. 20 lbs
- Box Dimensions: 23" x 17" x 11"
- Full Pallet Quantity: 20 boxes
- Pallet Dimensions: 48" x 40" x 73"

Description

The U-Anchor 3000-PVC is a lightweight rooftop attachment system consisting of a thermoplastic target membrane and a U-Anchor 3000 series plate. The plate is factory welded to the target membrane and a matching thermoplastic cover membrane is applied over the plate and onto the target membrane, encapsulating the plate. The U3000-PVC provides a positive, watertight, manufacturer accepted attachment for mechanically attached and fully adhered PVC roofing systems.

Additionally, the U3000-PVC acts as an effective expansion joint at each rooftop attachment point and minimizes stress to roof components.

Advantages

- Extremely strong and lightweight
- Fast installation, approximate rate of 12 per man hour
- Installs on any flat surface

U-Anchor Attachment

The U3000-PVC is attached to a fully adhered roofing system by hot air welding around the perimeter edge consistent with the specified roofing manufacturer's hot air welding specifications.

Equipment Attachment

To securely mount your rooftop equipment to the U-Anchor, after its installed, the connection nut must be fastened to approximately 20-25 torque pounds.

Use a calibrated torque wrench during install to ensure appropriate results are achieved.

Testing / Approvals

- Accepted - All Major Roofing Manufacturers

Individual deck assembly reports available upon request.

Ratings

Results are base on plate performance only.

- Ultimate Load - Shear: Pending
- Ultimate Load - Tension: Pending

*Test was performed in accordance with:
ASCE 7-10 ASTM E330-02 (2010) TAS 1178*

Warranty

- Standard 20 Year Material Only Warranty

* Specified option is standard. Custom options may be available for additional charge. Lead times may apply depending on roofing manufacturer and product availability.