HTD 0640

HVAC TIE-DOWN SECUREMENT



AP Solution **HTD 0640 HVAC Tie-Down** secures your rooftop unit to the structure. Tie-downs can be installed with the system or retrofitted as needed.

Winds as light as 50-60 mph can dislodge your outdoor unit from its base, causing damage to the unit and your roof. The HTD 0640 protects your unit from damage and prevents costly repairs.

The U-Anchor[™] 2000 Series Attachments by Anchor Products have proven effective in securing HVAC equipment in harshest conditions caused by earthquakes or hurricanes.

U-Anchor 2000 Series

HVAC SYSTEMS SECUREMENT

ASCE 7-16 code requires all rooftop equipment to be bolted, welded, or otherwise positively fastened without consideration of frictional resistance.



FEATURES:

- » Attaches safely to single-ply, asphalt and coated roofs without damaging the roof using a U-Anchor 2000 Series Attachment.
- » The ultimate force resistance of each 2000 series U-Anchor is approximately 2,713 lbs. in tension and 4,339 lbs. in shear.
- » The 3/16" stainless steel 7x19 aircraft cable offers a breaking strength of approximately 3700 lbs. (Other wire rope options available upon request.)
- » The U-Anchor can be used with all HVAC Equipment.
- » All exposed components and hardware are stainless steel, aluminum, or other non-corrosive materials.

ADVANTAGES

- » Quick and easy install.
- » Stainless steel straps and cables ensure that the metal will not corrode or deteriorate in the harshest of environments.
- » The HVAC Tie-Down Securement using the U-Anchors will not void the roof warranty.

Contact **Anchor Products Technical Services** for assistance with your custom mounting solution.

WARNING! The products included/described herein are protected by patents that are exclusively licensed to Anchor Products (visit www.anchorp.com/patents for details). Any use of Anchor's products for anything other than their expressed intended purpose or installation other than according to the written instructions provided by Anchor Products shall void all warranties, representations and promises related to the products and Anchor Products disclaims any and all liability associated with the products in such an event. If you have any questions about the proper use or installation of the products. Please contact Anchor Products at 888-575-2131.