

The U2400-PVC is a lightweight rooftop attachment system that is leak-proof by design. It is accepted by major roofing manufacturers and is included in their warranties. The U-Anchor membrane is matched to any PVC roof type, manufacturer, or color, making it versatile for any rooftop project.



U-ANCHOR®



Front

U2400-PVC



Back

Product Description

The U2400-PVC is a lightweight rooftop attachment system consisting of a U-Anchor 2000 Series plate and cover membrane. The cover membrane is factory sealed to the top of the plate. The U2400-PVC provides a positive, watertight, manufacturer accepted attachment for mechanically attached or fully adhered PVC single-ply membranes.

The U2400-PVC secures rooftop equipment quickly, safely, and effectively.

U-Anchor Advantages

- · Extremely strong
- Lightweight
- Fast installation installs in less than five minutes
- Can be installed on any surface from flat on the roof to vertical on a parapet wall
- Completely watertight when installed properly

Equipment Attachment

- The U2400-PVC is attached by fastening through the roofing assembly into the structural decking with 2-8 approved fasteners. The membrane cover is then hot air welded around the perimeter to the roof membrane. Fastener selection is dictated by the system assembly, deck type, and the project engineer.
- To securely mount your rooftop equipment to the U-Anchor, after it is installed, the connection nut must be fastened to approximately 20-25 lbf-ft. Use a calibrated torque wrench during the installation to ensure appropriate results are achieved. Excessive torque may damage the U-Anchor.
- Material Compatibility:

The U-Anchor bolt is stainless steel and all attachments provided by Anchor Products are tested as a system and designed to be compatible. Refer to installation instructions and the specified roofing material manufacturer requirements before installing.

Manufacturer's Warranty

 Anchor Products Warranty Standard 20-Year Limited Material Only Warranty



© Anchor Products

6316 Airport Fwy. Ste. D, Haltom City, TX 76117

Connections That Last





Make the right choice for rooftop attachments with the U-Anchor. It's a one-of-a-kind attachment for commercial rooftop equipment securement.



Codes & Approvals



FM 4481 - Anchors for roof mounted equipment

FM Approval with selected membranes



Testing

- Results are based on plate performance only.
 Ultimate Load Shear: 4293 lbs.
 Ultimate Load Tension: 2712 lbs.
- Tested in accordance with FM 4481 Section 4.1 over 1/2" Steel. Assembly specific results may vary. Please contact Anchor Products[®] directly for additional testing results and information.
- The shear value is obtained by testing at the base of the bolt. Account for the moment force of any attachment that increases the height of the connection point.

Product Specs

· Bolt

3/8"-16 x 1-3/8" Bolt*

Material Type: 304 Stainless Steel

Plate

Diameter: 5.5"

Fastener Hole Diameter: 0.265" (8 holes) Fastener Hole Pattern: 4.125" Diameter

Material Thickness: 0.047"

Material Type: G90 Galvanized Steel

Cover Membrane

Manufacturer: Brand and Non-Brand Specific Color: White (Other colors available)

Length: 11.75" Width: 11.75"

Thickness: Default 60 mils


Patents


Visit www.anchorp.com/resources/patents

Packaging Specs

- Sold Individually or Full Box Quantity
- · Individual Weight: Approx. 0.6 lbs.
- Full Box Quantity: 10 units
- Box Weight: Approx. 9.8 lbs.
- Box Dimensions: 13" x 11" x 13"
- Full Pallet Quantity: 60 boxes
- Pallet Dimensions: 40" x 48" x 69"

U2400-PVC Dimensional Drawing









Call Us Now! 888-575-2131

For Warranty Information anchorp.com

* Specified bolt option is standard. Custom options may be available for additional charge. Lead times may apply depending on roofing manufacturer and product availability.

© Anchor Products

6316 Airport Fwy. Ste. D, Haltom City, TX 76117

Connections That Last

